

## **480TN DOOR MODEL**



### **CHAPTER DESCRIPTION (STANDARD MODEL)**

Manual sliding door for positive temperature (chilled application) mod. **480/TN**, **92mm** door-leaf thickness insulated with injected polyurethane foam, standard covering with galvanized white steel RAL 9010, floor level threshold S/3, to be fixed on panel by MTH frame.

All dimensions available.

### **USE**

Suitable for any room for preserving, processing and seasoning at positive temperature (+1°C min.).

They are used for meat processing plants, dairies, fruit and vegetable preserving, slaughter houses, food warehouses, ham and cheese stores, fresh fish, fish processing rooms, fish stores, milk and its derivatives industry, ice cream/syrup industry.

### **STANDARD TECHNICAL FEATURES**

- Door leaf: inside polyurethane foam 42 kg/mc density, pre-painted white RAL9010 steel covering.
- Door leaf edge: extruded anodized aluminium profile with special perimeter rubber gasket. Stainless steel/Plastic hinges positioned on the sides grant an hermetic closing.
- Door frame: extruded PVC profiles composed by frame, side frames (depending by panel thickness), counter frame.
- Two door-blades version available.

### **AVAILABLE OPTIONS**

- Door leaf:
  - different plastified steel colours (red, green, blue, yellow );
  - stainless steel covering AISI 304 type (with different surfaces by request);
  - white glass board;
  - plastified stainless steel (with different colours by request);
  - s/2 threshold (steel corner);
  - s/5 threshold (step with height on request).
  - MTH door lock with key;
- Door leaf edge: stainless steel.
- Porthole rectangular or round, stainless steel (or polyethylene) kick plate, frame for Brick wall (see attached dwg);
- Complete Automatic MTH System ® with all necessary components.

### **HOW TO ORDER**

- Clear opening or panel hole dimensions;
- Opening direction (seeing hinges side);
- Thickness of the panel wall;
- Specify options.