

## Service doors (Technical door)



### CHAPTER DESCRIPTION (STANDARD MODEL)

**Semi-insulated** hinged door mod. "Service", 42 mm door-leaf thickness insulated with injected polyurethane foam, 42 Kg/mc P.U. density, standard covering with galvanized white steel RAL 9010, floor level threshold S/3 type, to be fixed on panel by aluminium MTH frame. All dimensions available.

#### USE

Especially for medicines processing medicines or freezing blood processing rooms from offices area, noisy places from rooms which need to be soundproofed as in the hospitals (soundproof), Cleanroom Cold rooms from offices(thermal-insulation) In the telephone and computer industry, the testing rooms from offices.

They are even used for lavatories and dressing rooms.

### STANDARD TECHNICAL FEATURES

- Door leaf: inside polyurethane foam 42 kg/mc density, pre-painted white RAL9010 steel covering.
- Door leaf edge: extruded anodized aluminium profile with special perimeter rubber gasket. Aluminium hinges positioned on the sides grant an hermetic closing. Black plastic handle with key-lock included.



- Door frame: extruded Anodized Aluminium profiles composed by frame, side frames (depending by panel thickness), counter frame.
- Two door-blades version available with special profile male/female designed especially for this door model.

### AVAILABLE OPTIONS

- Door leaf:
- different plastified steel colours (red, green, blue, yellow );
  - stainless steel covering AISI 304 type (with different surfaces by request);
  - white glass board;
  - plastified stainless steel (with different colours by request);
  - Door leaf edge: stainless steel.
  - Porthole, Open/close device, aluminium handle, door closer, stainless steel (or polyethylene) kick plate, anti-panic bar, frame for Brick wall (see attached dwg)..

### HOW TO ORDER

- Clear opening or panel hole dimensions;
- Opening direction (seeing hinges side);
- Thickness of the panel wall;
- Specify options.