

## TO AND FRO DOOR MODEL



### CHAPTER DESCRIPTION (STANDARD MODEL)

Semi-insulated hinged door type "TO & FRO", 42 mm door-leaf thickness insulated with injected polyurethane foam, 42 Kg/mc P.U. density, standard covering with galvanized white steel RAL 9010, floor level threshold S/3, oval porthole in Lexan 25 x 75 h. (mm) on each leaf, with stainless steel protection H. 300 (mm) on both sides, to be fixed on panel with MTH frame.

All dimensions available.

### USE

To and fro Semi-insulating door: mainly used to separate processing rooms (meat, dairies, fruit preserving) from places of transit of peoples or trolleys.

For example: the trolleys are loaded in the processing rooms and then pass through special aisles and move outdoor. To separate these areas such doors (with 1 or 2 wings) are used.

### STANDARD TECHNICAL FEATURES

- Door leaf: inside polyurethane foam 42 kg/mc density, pre-painted white RAL9010 steel covering.
- Door leaf edge: extruded anodized aluminium profile with special perimeter rubber gasket. Stainless steel/Plastic hinges positioned on the sides grant an hermetic closing. Polycarbonate window included.
- Door frame: extruded PVC profiles composed by frame, side frames (depending by panel thickness), counter frame.
- Two door-blades version available.

### AVAILABLE OPTIONS

- Door leaf:
  - different plastified steel colours (red, green, blue, yellow);
  - stainless steel covering AISI 304 type (with different surfaces on request);
  - white glass board;
  - plastified stainless steel (with different colours by request);
- Door leaf edge: stainless steel.
- Pvc bumper protection (150 mm/400 heighth), polyethylene door leaf, railway passage for meat factories;
- Frame for brick walls/"C" profile frame. – Railway passage for meat.

### HOW TO ORDER

- Clear opening or panel hole dimensions;
- Opening direction (hinges side from outside);
- Thickness of the panel wall;
- Specify options.